

## FS-414C (Art.262C) FIBA approved.

Pair of statistics panels (side displays) showing the Player No., Fouls/Penalties and Points of 14 players on the 2 teams.

Ideal for Basketball, Volleyball, 5-a-Side Football (Futsal), Waterpolo, etc..

### Functions displayed for each player (14 players per team):

**Player number:** [0-99], digits 15cm high.

**Fouls/Penalties:** [4 indicator lights + 1 red], diameter 3.2cm.

**Points:** [0-99], digits 15cm high.

### Technical characteristics for both panels:

- **Dimensions and weight:** 120x320x11.5cm, 86kg.
- **Distance and readability angle:** 70m (230ft), 150 degrees.
- **No front protection cover required.** Complies with DIN 18032-3 and UNI 9554:1989 standards on "resistance to damage from balls". You save on the cost of a protective cover, visibility is completely preserved, and access to the scoreboard is easy. [YouTube video](#)
- **It fulfils the FIBA level 2 requirements** if used together with the scoreboards **FS-120N** or **FS-130N** ([info](#), [FIBA certificate](#)). It can be used together with other models for creating large scoreboards displaying various information ([info](#)).
- **Shipping is cheap and fast.** The scoreboard is especially designed to be taken apart into smaller modules that are easy to assemble. This allows it to be shipped via all major couriers at a low cost and with faster delivery times to all countries.
- **Easy to install.** Technical instructions in 5 languages. Provided with bolts and brackets for wall mounting.
- **Supplied with serial cable** 4m in length to connect to the main electronic scoreboard (**FS-100/100N**, **FS-110/110N**, **FS-120/120N**, **FS-130/130N**) or to a Radio Receiver (art.265-20). See ACCESSORIES.
- **Robust container** made from powder-coated aluminum. Front panel made from anti-glare polycarbonate.
- **Views are easily accessible** from the front, built with high-quality, wide-angle SMD LEDs with an average life of 100,000 hours!
- **Control Console (not included).** Controlled via the Control Console (see ACCESSORIES) of the electronic scoreboard above it.
- **Anti-moisture coating** of the electronic boards, mandatory for swimming-pool and ice-rink installations. Please specify this option when ordering..
- **Guarantee:** 2 years ([info](#)).
- **Power supply:** 100-240Vac, 50-60Hz, 290VA. Select the type of plug for the power supply cord when ordering.

### ACCESSORIES (not included):

- **Scoreboard Control Console: Art.308-01 Console-700**

User-friendly multisport touchscreen console for FC, FS, FW, TM, FOS series electronic scoreboards. Wireless or wired communication. 14-hour average life internal battery.

- **FS2 Radio Receiver for FS scoreboards (art.265-20).** Receives via radio the data transmitted by the control console and distributes the signal to one or more scoreboards via cable. Reliable wireless communication: by 2.4GHz FHSS (Frequency Hopping Spread Spectrum) radio transmission to avoid interferences. The use of a wireless system reduces costs by eliminating the need of a cable connection between console and scoreboards. >> [Radio Receiver installation manual](#)



Art.262B

**FS-414B statistics panels, 2x14 Players (Player No. + Fouls)**

Size: 2x 120x320x11,5cm. - Weight: 168kg.



Art.262C

**FS-414C statistics panels, 2x14 players (Player No. +Fouls +Points)**

Size: 2x 120x320x11,5cm. - Weight: 172kg.